

RUST-OLEUM®
INDUSTRIAL



ASPHALT REPAIR

Immediately pot-hole repair



- Simple to use - no mixing required
- Repairs can be driven over immediately after application
- Ideal for repairs 10 mm – 70 mm
- Coverage approx. 0.5 m² per 25 kg at 24 mm thick
- Withstands heavy traffic

footer_main_page_line_one

footer_main_page_line_two

ASPHALT REPAIR

POPIS PRODUKTU (DLHÝ)

A durable bitumen-based patch repair for use on exterior pot-holed asphalt and concrete based on polished aggregate together with liquid binder based on bitumen plus resins and adhesives. Ideal for potholes in roads, car parks, paths and other bituminous and concrete surfaces.

ODPORÚČANÉ POUŽITIE

Ideal for pot-holes in roadways, vehicle parks, loading docks, paths, airfields etc, on bituminous and concrete surfaces.

ODPORÚČANÁ HRúbKA SUCHÉHO FILMU

between 25 and 100 mm

TEORETICKÁ SPOTREBA

At a film thickness of 24 mm 25 kg will cover approximately 0.5m². The product can be applied up to 100mm film thickness.

PRAKTICKÁ VÝDATNOSŤ

Practical coverage depends on many factors such as porosity and roughness of the substrate and material losses during application.

PRÍPRAVA POVRCHU

Remove all loose material and surface water, oil etc. Apply the primer with a brush on the prepared surface.

PODMIENKY APLIKÁCIE

Temperature of air, substrate and coating material between 5 and 25°C. At lower temperatures the product will be tougher and is therefore more difficult to apply.

APLIKÁCIA A RIEDENIE: HRABLAMI/HRABLIČKOU

Do not dilute the product.

SKLADOVATEĽNOSŤ

Minimum of 2 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 25°C.

last_updated: 07/02/2025

footer_data_colors_pack_sizes: footer_data_colors_pack_sizes.value

footer_data_disclaimer: footer_data_disclaimer.value

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T: +31 (0) 165 593 636
F: +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T: +44 (0)1914 113 146
F: +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chiène
95322 Herblay
France
T: +33(0) 130 40 00 44
F: +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T: +32 (0) 13 460 200
F: +32 (0) 13 460 201
info@rust-oleum.eu