

RUST-OLEUM®
INDUSTRIAL



COMBICOLOR® THINNER STANDARD



Thinner for Rust-Oleum 7300 CombiColor® product range.

- Easy to pour
- Reclosable packaging
- Special for CombiColor Original and Hammertone, also for cleaning and degreasing

footer_main_page_line_one

footer_main_page_line_two

COMBICOLOR® THINNER STANDARD

POPIS PRODUKTU (DLOUHÝ)

Special thinner for Rust-Oleum 7300 CombiColor® product range. Optimal solvent combination for 7300-product range. Good thinning properties.

DOPORUČENÉ POUŽITÍ

Thinner for 7300 Combicolor topcoats and primers.

POZNÁMKY

For air-atomised spraying of CombiColor Hammertone topcoats use the special thinner 7302

DATA SAFETY DATA

Úroveň těžkých organických

látek: 820 g/l

Poznámky k bezpečnosti: Consult Safety Data Sheet and Safety Information printed on the can.

DOBA POUŽITELNOSTI

Minimum of 5 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

last_updated: 07/02/2025

footer_data_colors_pack_sizes: footer_data_colors_pack_sizes.value

footer_data_disclaimer: footer_data_disclaimer.value

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu