

RUST-OLEUM®
INDUSTRIAL



COATING PRT®

Flexible, long lasting finish for roofs or walls

- Flexible durable paint for renovation of roofs, ideal for making roofs white
- Resistant to UV, acid rain, heat, frost and pollution
- Ideal topcoat for DACFILL® or NOXYDE® to reduce dirt pickup
- Can be used in high humidity areas
- Can also be used on walls

footer_main_page_line_one

footer_main_page_line_two

COATING PRT®

POPIS PRODUKTU (DLOUHÝ)

Single pack high performance topcoat for walls and roofs, ideal for moist conditions and making roofs white. Also ideal to minimise dirt retention on DACFILL® or NOXYDE®.

DOPORUČENÉ POUŽITÍ

- Coating of inner and outer walls that can be exposed to high humidity, f.i. bathrooms, kitchens, etc.
- Topcoat on Dacfill (improved resistance against stagnating water and less dirt retention) or on Noxyde (less dirt retention)

TECHNICAL DATA

Hustota (g/cm ³):	1,12
Úroveň lesku:	Satin
Obsah pevných látek v hmotnosti:	48%
Obsah pevných látek v objemu:	42%

DRY TIMES BY 20

Dotykem suché:	3 hours
Suché na manipulaci:	4 hours
Suchý nátěr:	24 hours
Plně vytvrzené:	24 hours

DOPORUČENÁ TLOUŠŤKA MOKRÉHO FILMU

140 µm

DOPORUČENÁ TLOUŠŤKA SUCHÉHO FILMU

60 µm

TEORETICKÁ SPOTŘEBA

7 m²/l

PRAKTICKÁ SPOTŘEBA

Practical coverage depends on many factors such as porosity and roughness of the substrate and material losses during application. If the product is applied directly on bitumen felt, the consumption can be considerably higher. Account must be taken of 3.5 m² / l. Apply a test patch before starting the works in order to determine the actual practical consumption.

PŘÍPRAVA POVRCHU

Clean the substrate. Allow to dry, any previous coatings must be completely dry.

NÁVOD K POUŽITÍ

To ensure homogeneity, coating materials should be thoroughly stirred prior to use.

PODMÍNKY POUŽITÍ

Work in a dry and well-ventilated area.

APLIKACE A ŘEDĚNÍ: ŠTĚTEC

All types.

APLIKACE A ŘEDĚNÍ: VÁLEČEK

Short nap-mohair roller.

APLIKACE A ŘEDĚNÍ: BEZVZDUCHOVÝ SPREJ

Nozzle: 4/15 - Pressure: 100 bars.

APLIKACE A ŘEDĚNÍ: VZDUCHOVÝ ATOMIZOVANÝ SPREJ

Do not dilute.

ČIŠTĚNÍ ZAŘÍZENÍ / ROZLITÍ

Thinner 22 or white spirit.

POZNÁMKY

Reversible paint system, this means that the product dissolves in its own solvent. Can be applied on new concrete.

DATA SAFETY DATA

Úroveň těžkých organických látek:	481 g/l
VOC readymix:	499 g/l
Kategorie VOC:	A/í
Limitní hodnota VOC:	500 g/l
Grenelle:	Exterior
Poznámky k bezpečnosti:	Consult Safety Data Sheet and Safety Information printed on the can.

DOBA POUŽITELNOSTI

Minimum of 5 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

last_updated: 07/02/2025

footer_data_colors_pack_sizes: footer_data_colors_pack_sizes.value

footer_data_disclaimer: footer_data_disclaimer.value

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu