

**RUST-OLEUM®**  
INDUSTRIAL



## DACFILL® PU TOPCOAT



# Seamless waterproofing membrane for roofs

- Easy to apply and detail
- Compatible with most existing roof membranes
- Permanent elastomeric and seamless
- Excellent resistance to ponded water
- Fibre reinforced for maximum film strength

footer\_main\_page\_line\_one

footer\_main\_page\_line\_two

# DACFILL® PU TOPCOAT

## POPIS PRODUKTU (DLOUHÝ)

Dacfill PU top coat is a low odour, cold applied single pack, ultra high solids moisture activated elastomeric urethane coating.

## DOPORUČENÉ POUŽITÍ

For application as the top coat in Dacfill PU roof waterproofing membrane systems. A high build, heavy duty coating, almost free from solvent odour that provides durable, long term protection for roofs. To be used as a fully reinforced weatherproofing system.

## DOPORUČENÝ SYSTÉM

3388 Metal Primer  
3377 Binder Sealer  
Dacfill PU Embedment coat  
Dacfill Fleece  
Dacfill PU Top coat  
Dacfill PU Fibres

## TECHNICAL DATA

Hustota (g/cm<sup>3</sup>): 1.45  
Obsah pevných látek v objemu: 87%

## DRY TIMES BY 20

Dotykem suché: 4 hours  
Suché na manipulaci: 24 hours  
Suchý nátěr: min. 24 hours, max. 7 days

## DOPORUČENÁ TLOUŠŤKA SUCHÉHO FILMU

0.45-0.7 mm per coat (depending on the system)

## TEORETICKÁ SPOTŘEBA

1-2m<sup>2</sup> per litre per coat

## PRAKTICKÁ SPOTŘEBA

Dependent on surface profile, reinforcement where applicable etc.

## PŘÍPRAVA POVRCHU

Inspect all surfaces to assess soundness of existing substrates or coatings. Where necessary prepare test areas. Roof surfaces must be clean, dry and free from all loose debris and be carried out before application of the coating. All areas of fungal growth, moss etc should be treated with AMW Fungicidal Wash and neutralised residues removed. Apply over Dacfill Fleece reinforced Embedment Coat (where necessary). Priming, where necessary should be carried out using suitable compatible materials. Contact Rust-Oleum Technical Department for further advice.

## NÁVOD K POUŽITÍ

Brush or roller. May be used as the carrier for Dacfill glass fibre reinforcement matting on localised repairs.

## PODMÍNKY POUŽITÍ

Do not apply if rain is imminent.

## APLIKACE A ŘEDĚNÍ: ŠTĚTEC

Do not thin

## APLIKACE A ŘEDĚNÍ: VÁLEČEK

Do not thin

## ČIŠTĚNÍ ZAŘÍZENÍ / ROZLITÍ

Thinner 150

## POZNÁMKY

Overcoating must be carried out within the timescale overleaf otherwise further preparation may be necessary.

For any information regarding options of guarantee with this system, please contact Technical Service.

This product does contain isocyanates. Users must follow mandatory training to comply with EU 2020/1149 Restriction 74.

## DATA SAFETY DATA

Úroveň těkavých organických  
látek: <175g/l  
Kategorie VOC: Cat A/i  
Limitní hodnota VOC: EU limit 500 g/l

## DOBA POUŽITELNOSTI

12 months from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

last\_updated: 07/02/2025

footer\_data\_colors\_pack\_sizes: footer\_data\_colors\_pack\_sizes.value

footer\_data\_disclaimer: footer\_data\_disclaimer.value

**Rust-Oleum Netherlands B.V.**  
Zilverenberg 16  
5234 GM 's-Hertogenbosch  
The Netherlands  
T: +31 (0) 165 593 636  
F: +31 (0) 165 593 600  
info@rust-oleum.eu

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T: +44 (0)1914 113 146  
F: +44 (0)1914 113 147  
info@rust-oleum.eu

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95322 Herblay  
France  
T: +33(0) 130 40 00 44  
F: +33(0) 130 40 99 80  
info@rust-oleum.eu

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T: +32 (0) 13 460 200  
F: +32 (0) 13 460 201  
info@rust-oleum.eu