

**RUST-OLEUM®**  
INDUSTRIAL



## GROUND MARKER FLUORESCENT



# For marking & locating in construction & civil engineering

- Optimised for ground marking
- Spray through cap for ease of use
- Easier writing
- Quick drying (5 - 10 minutes)

footer\_main\_page\_line\_one

footer\_main\_page\_line\_two



# GROUND MARKER FLUORESCENT

## POPIS PRODUKTU (DLOUHÝ)

For quick and easy marking of construction and excavation sites, underground utilities and for traffic safety. Optimised for ground marking. By means of the 360° valve the aerosol is sprayable in all directions. RUST-OLEUM® Spot Marking Aerosol is based on a fast drying acrylic resin. All products in this range are aromatic free and based on lead- and chromate free pigments.

## DOPORUČENÉ POUŽITÍ

RUST-OLEUM® Spot Marking Aerosol 2800 can be used on metal, concrete, asphalt, gravel, soil and grass, etc. RUST-OLEUM® Spot Marking Aerosol 2800 is not water-soluble and should be used in light industrial exposures, normal humidity and interior applications. RUST-OLEUM® Spot Marking Aerosol 2800 is designed for quick and easy marking of construction and excavation sites, underground utilities and for traffic safety

## TECHNICAL DATA

Úroveň lesku: Matt  
Tepelná odolnost: 100°C (dry heat)

## DRY TIMES BY 20

Dotykem suché: 5 minutes  
Suché na manipulaci: 30 minutes

## TEORETICKÁ SPOTŘEBA

500 ml: 1,5 m<sup>2</sup> per spray can at 25 µm dry

## PRAKTICKÁ SPOTŘEBA

Practical coverage depends on many factors such as porosity and roughness of the substrate and material losses during application.

## PŘÍPRAVA POVRCHU

Remove dirt, grease, oil and all other surface contaminants by appropriate means. The surface must be clean and dry during application.

## PODMÍNKY POUŽITÍ

For good results the relative humidity shall be below 85% and the temperature of the can and substrate above 0°C.

## APLIKACE A ŘEDĚNÍ: AEROSOL

Shake vigorously for at least one minute after the rattle of mixing ball is heard. Shake frequently during use. It is not possible to clean the spray button in the usual way. Due to the use of the 360° valve this is not necessary.

## DOBA POUŽITELNOSTI

Minimum of 3 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

last\_updated: 07/02/2025

footer\_data\_colors\_pack\_sizes: footer\_data\_colors\_pack\_sizes.value

footer\_data\_disclaimer: footer\_data\_disclaimer.value

**Rust-Oleum Netherlands B.V.**  
Zilverenberg 16  
5234 GM 's-Hertogenbosch  
The Netherlands  
T : +31 (0) 165 593 636  
F : +31 (0) 165 593 600  
info@rust-oleum.eu

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T : +44 (0)1914 113 146  
F : +44 (0)1914 113 147  
info@rust-oleum.eu

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chiène  
95322 Herblay  
France  
T : +33(0) 130 40 00 44  
F : +33(0) 130 40 99 80  
info@rust-oleum.eu

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T : +32 (0) 13 460 200  
F : +32 (0) 13 460 201  
info@rust-oleum.eu