

RUST-OLEUM®
INDUSTRIAL



MULTI MARKER 360°



For 360° marking in construction and engineering

- Optimised for 360° spraying
- Spray through cap for ease of use
- Easier writing
- Quick drying (5 - 10 minutes)

footer_main_page_line_one

footer_main_page_line_two

MULTI MARKER 360°

POPIS PRODUKTU (DLOUHY)

For quick and easy marking of construction and excavation sites, underground utilities and for traffic safety. Optimised for ground marking. By means of the 360° valve the aerosol is sprayable in all directions. RUST-OLEUM® Multimarker is based on a fast drying acrylic resin. All products in this range are aromatic free and based on lead- and chromate free pigments.

Available in RAL colours (750ml) & fluo (500ml)

DOPORUČENÉ POUŽITÍ

RUST-OLEUM® Multimarker 360° can be used on metal, concrete, asphalt, gravel, soil and grass, etc. RUST-OLEUM® Multimarker 360° is not water-soluble and should be used in light industrial exposures, normal humidity and interior applications. RUST-OLEUM® Multimarker 360° is designed for quick and easy marking of construction and excavation sites, underground utilities and for traffic safety

DRY TIMES BY 20

Dotykem suché: 5 min
Suché na manipulaci: 30 min

TEORETICKÁ SPOTŘEBA

500 ml: 1,5 m² per spray can at 25 µm dry
750 ml: 2,25 m² per spray can at 25 µm dry (depending on colour)

PRAKTICKÁ SPOTŘEBA

Practical coverage depends on many factors such as porosity and roughness of the substrate and material losses during application.

PODMÍNKY POUŽITÍ

For good results the relative humidity shall be below 85% and the temperature of the can and substrate above 0°C.

APLIKACE A ŘEDĚNÍ: AEROSOL

Shake vigorously for at least one minute after the rattle of mixing ball is heard. Shake frequently during use. It is not possible to clean the spray button in the usual way. Due to the use of the 360° valve this is not necessary.

DOBA POUŽITELNOSTI

Minimum of 3 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

last_updated: 01/10/2024

footer_data_colors_pack_sizes: footer_data_colors_pack_sizes.value

footer_data_disclaimer: footer_data_disclaimer.value

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM s-Hertogenbosch
The Netherlands
T: +31 (0) 165 593 636
F: +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T: +44 (0)1914 113 146
F: +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T: +33(0) 130 40 00 44
F: +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T: +32 (0) 13 460 200
F: +32 (0) 13 460 201
info@rust-oleum.eu