

**RUST-OLEUM®**  
INDUSTRIAL



## MULTI MARKER 360°

# For 360° marking in construction and engineering

- Optimised for 360° spraying
- Spray through cap for ease of use
- Easier writing
- Quick drying (5 - 10 minutes)

LE SAVOIR-FAIRE EN PROTECTION™

[WWW.RUST-OLEUM.EU](http://WWW.RUST-OLEUM.EU)

# MULTI MARKER 360°

## DESCRIPTION

For quick and easy marking of construction and excavation sites, underground utilities and for traffic safety. Optimised for ground marking. By means of the 360° valve the aerosol is sprayable in all directions. RUST-OLEUM® Multimarker is based on a fast drying acrylic resin. All products in this range are aromatic free and based on lead- and chromate free pigments.

Available in RAL colours (750ml) & fluo (500ml)

## UTILISATION RECOMMANDÉE

RUST-OLEUM® Multimarker 360° can be used on metal, concrete, asphalt, gravel, soil and grass, etc. RUST-OLEUM® Multimarker 360° is not water-soluble and should be used in light industrial exposures, normal humidity and interior applications. RUST-OLEUM® Multimarker 360° is designed for quick and easy marking of construction and excavation sites, underground utilities and for traffic safety

## TEMPS DE SÉCHAGE À 20°C/HR 50%

Au toucher: 5 min  
Manipulable: 30 min

## CONSOMMATION THÉORIQUE

500 ml: 1,5 m<sup>2</sup> per spray can at 25 µm dry  
750 ml: 2,25 m<sup>2</sup> per spray can at 25 µm dry (depending on colour)

## CONSOMMATION PRATIQUE

Practical coverage depends on many factors such as porosity and roughness of the substrate and material losses during application.

## CONDITIONS D'APPLICATION

For good results the relative humidity shall be below 85% and the temperature of the can and substrate above 0°C.

## APPLICATION & DILUTION: AÉROSOL

Shake vigorously for at least one minute after the rattle of mixing ball is heard. Shake frequently during use. It is not possible to clean the spray button in the usual way. Due to the use of the 360° valve this is not necessary.

## DURÉE DE VIE

Minimum of 3 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

Date d'émission: 31/10/2024

**Couleurs et conditionnements disponibles:** Reportez-vous à la page produit concernée sur [www.rust-oleum.eu](http://www.rust-oleum.eu) pour avoir un aperçu des couleurs et des tailles d'emballage actuellement disponibles.

**Notion de responsabilité:** Les informations communiquées ici sont véridiques et exactes et sont fournies de bonne foi au meilleur de nos connaissances, mais sans garantie. Il est estimé que l'utilisateur se sera assuré lui-même de la compatibilité de nos produits avec son usage particulier. Rust-Oleum Europe ne sera en aucun cas tenue pour responsable quant aux dommages consécutifs ou indirects. Les produits doivent être stockés, manipulés et appliqués conformément aux conditions respectant les recommandations de Rust-Oleum Europe détaillées dans le dernier exemplaire de la fiche technique du produit. Il incombe aux utilisateurs de veiller à disposer de l'exemplaire actuel. Les dernières versions de la fiche technique du produit sont disponibles gratuitement et peuvent être téléchargées sur [www.rust-oleum.eu](http://www.rust-oleum.eu) ou sur demande adressée à notre département Service à la clientèle. Rust-Oleum Europe se réserve le droit de modifier les propriétés de ses produits sans avis préalable.

**Rust-Oleum Netherlands B.V.**  
Zilverenberg 16  
5234 GM 's-Hertogenbosch  
The Netherlands  
T : +31 (0) 165 593 636  
F : +31 (0) 165 593 600  
info@rust-oleum.eu

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T : +44 (0)1914 113 146  
F : +44 (0)1914 113 147  
info@rust-oleum.eu

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95322 Herblay  
France  
T : +33(0) 130 40 00 44  
F : +33(0) 130 40 99 80  
info@rust-oleum.eu

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T : +32 (0) 13 460 200  
F : +32 (0) 13 460 201  
info@rust-oleum.eu