

**RUST-OLEUM®**  
INDUSTRIAL



## PRIMER 44HS®

# Primer for brittle or weathered roofs, floors, walls

- Excellent fixation for stabilizing loose particles
- Prevents porous substrates from absorbing expensive coatings
- Flexible paint withstands temperature changes
- Quickly water-resistant (1 hour after application at 20 °C)
- Can be used on roofs, floors and walls

footer\_main\_page\_line\_one

footer\_main\_page\_line\_two

# PRIMER 44HS®

## POPIS PRODUKTU (DLHÝ)

Ready to use single pack binding primer based on chlorinated rubber improves adhesion of coatings on porous mineral surfaces.

## ODPORÚČANÉ POUŽITIE

Fixation layer for porous and unpainted mineral substrates.

## TECHNICAL\_DATA

Hustota (g/cm <sup>3</sup> ):	1,1
Úroveň lesku:	Gloss
Obsah pevných látok v hmotnosti:	45%
Obsah pevných látok v objeme:	32%

## DRY\_TIMES\_BY\_20

Na dotyk suché:	1 hour
Suché na manipuláciu:	1 hour
Suchý na opätovné natieranie:	24 hours
Úplne vytvrdnuté:	24 hours

## ODPORÚČANÁ HRúbKA MOKRÉHO FILMU

70 µm

## ODPORÚČANÁ HRúbKA SUCHÉHO FILMU

23 µm

## TEORETICKÁ SPOTREBA

14 m<sup>2</sup>/l

## PRAKTICKÁ VÝDATNOSŤ

10 - 15 m<sup>2</sup>/l. Practical coverage depends on many factors such as porosity and roughness of the substrate and material losses during application.

## PRÍPRAVA POVRCHU

Clean and degrease the substrate. If the substrate is an acrylic paint, this must NOT be recoated with Primer 44HS (the acrylic paint is affected by the solvents of Primer 44HS). In such a case, replace Primer 44HS with Pegafix.

## NÁVOD NA POUŽITIE

To ensure homogeneity, coating materials should be thoroughly stirred prior to use.

## PODMIENKY APLIKÁCIE

Apply in a dry and well-ventilated area. > 5°C, < 80% R.H.

## APLIKÁCIA A RIEDENIE: ŠTETEC

All types. Do not dilute.

## APLIKÁCIA A RIEDENIE: VALEC

All types. Do not dilute.

## APLIKÁCIA A RIEDENIE: BEZVZDUCHOVÉ STRIEKANIE

Do not dilute. Nozzle: 011 - 013. Pressure: 150 - 170 bars.

## APLIKÁCIA A RIEDENIE: VZDUCHOVO ATOMIZOVANÝ SPREJ

Do not dilute.

## ČISTENIE ZARIADENIA / POSTRIEKANIE

Thinner 22.

## POZNÁMKY

Ready for use. Do not dilute. Reversible paint system, this means that the product dissolves in its own solvent.

## DATA SAFETY DATA

Úroveň VOC:	599 g/l
VOC readymix:	599 g/l
Kategória VOC:	A/h
Limit VOC:	750 g/l
Poznámky k bezpečnosti:	Consult Safety Data Sheet and Safety Information printed on the can.

## SKLADOVATEĽNOSŤ

Minimum of 2 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

last\_updated: 07/02/2025

footer\_data\_colors\_pack\_sizes: footer\_data\_colors\_pack\_sizes.value

footer\_data\_disclaimer: footer\_data\_disclaimer.value

**Rust-Oleum Netherlands B.V.**  
Zilverenberg 16  
5234 GM 's-Hertogenbosch  
The Netherlands  
T : +31 (0) 165 593 636  
F : +31 (0) 165 593 600  
info@rust-oleum.eu

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T : +44 (0)1914 113 146  
F : +44 (0)1914 113 147  
info@rust-oleum.eu

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95322 Herblay  
France  
T : +33(0) 130 40 00 44  
F : +33(0) 130 40 99 80  
info@rust-oleum.eu

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T : +32 (0) 13 460 200  
F : +32 (0) 13 460 201  
info@rust-oleum.eu