

**RUST-OLEUM®**  
INDUSTRIAL



## SUPERGRIP® 1K ANTI-SLIP FLOOR COATING



# Easy to apply 1 component anti-slip floor coating

- For foot traffic, interior and exterior
- Anti-slip additive is premixed in the coating
- For use on old concrete (>2yrs), metal and wood
- Touch dry after 6 hours

footer\_main\_page\_line\_one

footer\_main\_page\_line\_two

# SUPERGRIP® 1K ANTI-SLIP FLOOR COATING

## POPIS PRODUKTU (DLOUHÝ)

Easy to apply solvent based Alkyd anti-slip floor coating specially designed for applying on old (>2 years), dry concrete for interior and exterior use. The coating has a good resistance against abrasion and neutral detergents (no alkaline cleaning agents) and is resistance during short contact periods against lubricating oils, fuel, petrol etc.

## DOPORUČENÉ POUŽITÍ

7100 Floor Coating can be applied on concrete floors older than 2 years, which are completely clean and dry. It is not recommended to apply on smooth/dense concrete or concrete containing a damp repellent additive, which will prevent a good adhesion. 7100 Floor Coating can also be applied on old good adhering coatings. 7100 can be applied onto metal floors which have been correctly prepared and primed with a suitable Rust-Oleum metal primer.

## TECHNICAL DATA

Hustota (g/cm<sup>3</sup>): 1,0 - 1,1  
Úroveň lesku: Gloss  
Obsah pevných látek v objemu: 36 - 40%

## DRY TIMES BY 20

Dotykem suché: 6 hours  
Suchý nátěr: 24 hours  
Plně vytvrzené: 1 week

## DOPORUČENÁ TLOUŠŤKA MOKRÉHO FILMU

130 µm

## DOPORUČENÁ TLOUŠŤKA SUCHÉHO FILMU

50 µm

## TEORETICKÁ SPOTŘEBA

8,0 m<sup>2</sup>/l at 50 µm dry

## PRAKTICKÁ SPOTŘEBA

Practical coverage depends on many factors such as porosity and roughness of the substrate and material losses during application.

## PŘÍPRAVA POVRCHU

Remove oil, grease and other contaminations with Rust-Oleum 2901 EpoxyShield Cleaner/Degreaser for floors or high pressure- (steam) cleaning in combination with appropriate detergents. Sand old intact coatings to roughen the surface in order to establish a good adhesion. Check the compatibility with old intact coatings. During application the surface should be dry and clean. On porous concrete a first coat should be applied with 7100 diluted with ±10% volume 7301. Remove curing compounds by means of dust free blasting.

## NÁVOD K POUŽITÍ

To ensure homogeneity, coating materials should be thoroughly stirred prior to use.

## PODMÍNKY POUŽITÍ

Apply in a dry and well-ventilated area.

## APLIKACE A ŘEDĚNÍ: ŠTĚTEC

Sparingly, if required, with 10% volume 7301.

## APLIKACE A ŘEDĚNÍ: VÁLEČEK

Sparingly, if required, with 10% volume 7301. In case of roller application it can be necessary to apply 2 coats in order to obtain the recommended film thickness.

## ČIŠTĚNÍ ZAŘÍZENÍ / ROZLITÍ

Immediately after application using 7301.

## POZNÁMKY

Apply 7100 Floor Coating never on alkaline substrates.

Not suitable for use on tiles and in wet areas such as bathrooms.

## DATA SAFETY DATA

Úroveň těkavých organických  
látek: 456 g/l  
VOC ready mix: 485 g/l  
Kategorie VOC: A/i  
Limitní hodnota VOC: 500 g/l  
Poznámky k bezpečnosti: Consult Safety Data Sheet and Safety Information printed on the can.

## DOBA POUŽITELNOSTI

Minimum of 5 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

last\_updated: 07/02/2025

footer\_data\_colors\_pack\_sizes: footer\_data\_colors\_pack\_sizes.value

footer\_data\_disclaimer: footer\_data\_disclaimer.value

**Rust-Oleum Netherlands B.V.**  
Zilverenberg 16  
5234 GM 's-Hertogenbosch  
The Netherlands  
T: +31 (0) 165 593 636  
F: +31 (0) 165 593 600  
info@rust-oleum.eu

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T: +44 (0)1914 113 146  
F: +44 (0)1914 113 147  
info@rust-oleum.eu

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95322 Herblay  
France  
T: +33(0) 130 40 00 44  
F: +33(0) 130 40 99 80  
info@rust-oleum.eu

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T: +32 (0) 13 460 200  
F: +32 (0) 13 460 201  
info@rust-oleum.eu