

RUST-OLEUM[®]
— INDUSTRIAL —



THINNER 160

Solvent-based Thinner based on aromatic hydrocarbons

- Strong dilution capacity
- Can be used for many Rust-Oleum coatings
- Also ideal as a strong glue remover

footer_main_page_line_one

footer_main_page_line_two

THINNER 160

POPIS PRODUKTU (DLHÝ)

Solvent-based Thinner with strong dilution capacity based on aromatic hydrocarbons, used for many Rust-Oleum products for thinning and/or cleaning.

ODPORÚČANÉ POUŽITIE

Cleaning and/or Thinning solution for the following products:

- 1085 Cold Galvanising
- 8399 Hygienic Primer
- 9100 High performance epoxy
- 9169 Epoxy rust primer
- 9170/80 Epoxy metal primer
- B95 Flexible Epoxy

Cleaning (not Thinning) solution for the following products:

- 769 Damp-proof rust primer
- 1060/1080 High build metal primer
- 3202 Galvinoleum
- 3366 Rapid curing adhesion primer
- 5130 Damp surface primer
- 5401 Epoxy impregnation primer
- 5421 Epoxy impregnation primer
- 7201 Floorcoat PU primer
- 7500 Alkythane
- 9400 Rust-O-Thane SL
- 5500 Solvent-free epoxy
- 9700 Coldmax Rapid
- B95SL Flexible Epoxy
- GraffitiShield Polycoat
- ALL Epoxy-based concrete repair products

Other uses:

- Determine the nature of old coatings and ensure compatibility with future systems
- Determine presence of curing compounds
- Glue remover

POZNÁMKY

See the Product Data sheet of the respective product for further details.

DATA SAFETY DATA

Úroveň VOC: 890 g/l
Poznámky k bezpečnosti: Consult Safety Data Sheet and Safety Information printed on the can.

SKLADOVATEĽNOSŤ

Minimum of 5 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

last_updated: 07/02/2025

footer_data_colors_pack_sizes: footer_data_colors_pack_sizes.value

footer_data_disclaimer: footer_data_disclaimer.value

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chiène
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu