

RUST-OLEUM®
— INDUSTRIAL —



THINNER 191

Thinner based on aromatic hydrocarbons

- Correct solvent combination for Rust-Oleum polyurethane system 9600
- Strong diluting capacity
- Especially for spray applications

KNOW-HOW TO PROTECT™

WWW.RUST-OLEUM.EU

THINNER 191

DESCRIPTION

Solvent with high diluting capacity based on aromatic hydrocarbons, especially suitable for spray application dilution of polyurethane based coatings.

RECOMMENDED USE

Thinning solution for spray application of the following products:

- 569 Quick drying metal primer
- 769 Damp-proof rust primer
- 1060/1080 High build metal primer
- 7200 Floorcoat PU
- 7500 Alkythane
- 9600 Rust-o-Thane ®

APPLICATION CONDITIONS

Mix coating thoroughly. Thin only if necessary. Follow the thinning recommendations provided on the individual product label. Excessive thinning and the use of non-recommended thinners can be detrimental to service life and performance of the coating.

REMARKS

See the Product Data sheet of the respective product for further details.

SAFETY DATA

VOC level:

877 g/l

Remarks regarding safety:

Safety sheet available for professional user upon request.

SHELF LIFE

Minimum of 5 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

Date issued: 10/03/2025

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.

Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T: +31 (0) 165 593 636
F: +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)

Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T: +44 (0)1914 113 146
F: +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.

38, av. du Gros Chêne
95322 Herblay
France
T: +33(0) 130 40 00 44
F: +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.

Kolenbergstraat 23
3545 Zelem
Belgium
T: +32 (0) 13 460 200
F: +32 (0) 13 460 201
info@rust-oleum.eu