

RUST-OLEUM®
— INDUSTRIAL —



THINNER 633

Solvent based on aliphatic hydrocarbons

- Correct solvent combination for Rust-Oleum products based on alkyd resin binder
- Highly diluting capacity

KNOW-HOW TO PROTECT™

WWW.RUST-OLEUM.EU

THINNER 633

DESCRIPTION

Highly diluting solvent based on aliphatic hydrocarbons, suitable for alkyd based coatings.

DOPORUČENÉ POUŽITÍ

Cleaning and/or Thinning solution for the following products:

- 569 Quick drying metal primer
- 769 Damp-proof rust primer
- 1060/1080 High build metal primer
- 7200 Floorcoat PU
- 7500 Alkythane
- 8399 Hygienic Primer

APLIKACE A ŘEDĚNÍ: ŠTĚTEC

Can be diluted up to 10% volume

APLIKACE A ŘEDĚNÍ: VÁLEČEK

Can be diluted up to 10% volume

POZNÁMKY

See the Product Data sheet of the respective product for further details.

SAFETY DATA

Úroveň těžkých organických

látek: 755 g/l

Poznámky k bezpečnosti: Consult Safety Data Sheet and Safety Information printed on the can.

DOBA POUŽITELNOSTI

Minimum of 5 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

last_updated: 10/03/2025

footer_data_colors_pack_sizes: footer_data_colors_pack_sizes.value

footer_data_disclaimer: footer_data_disclaimer.value

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chiène
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu