

RUST-OLEUM[®]
— INDUSTRIAL —



THINNER 641

Thinner based on aromatic hydrocarbons

- Correct solvent combination for Rust-Oleum products based on an alkyd resin binder
- Strong diluting capacity
- For spray applications

KNOW-HOW TO PROTECT™

WWW.RUST-OLEUM.EU

THINNER 641

DESCRIPTION

Solvent with high diluting capacity based on aromatic hydrocarbons, especially suitable for spray application dilution in alkyd based coatings.

DOPORUČENÉ POUŽITÍ

Thinning solution for spray application of the following products:

- 569 Quick drying metal primer
- 769 Damp-proof rust primer
- 1060/1080 High build metal primer
- 7200 Floorcoat PU
- 7500 Alkythane

POZNÁMKY

See the Product Data sheet of the respective product for further details.

SAFETY DATA

Úroveň těkavých organických

látek: 860 g/l

Poznámky k bezpečnosti: Consult Safety Data Sheet and Safety Information printed on the can.

DOBA POUŽITELNOSTI

Minimum of 5 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

last_updated: 10/03/2025

footer_data_colors_pack_sizes: footer_data_colors_pack_sizes.value

footer_data_disclaimer: footer_data_disclaimer.value

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu