

RUST-OLEUM®
— INDUSTRIAL —



THINNER RL

Solvent based on isoparaffins

- Odourless

KNOW-HOW TO PROTECT™

WWW.RUST-OLEUM.EU

THINNER RL

DESCRIPTION

Odourless solvent-based thinner based on isoparaffins.

ODPORÚČANÉ POUŽITIE

Cleaning and/or Thinning solution for the following products:

- Pegamat RL

PODMIENKY APLIKÁCIE

Use in a dry and well ventilated area.

POZNÁMKY

Boiling range: 185 - 205°C. Kb-value: >25. Aromatic content: < 0,01%

SAFETY DATA

Úroveň VOC: 770 g/l
Poznámky k bezpečnosti: Consult Safety Data Sheet and Safety Information printed on the can.

SKLADOVATEĽNOSŤ

Minimum of 5 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

last_updated: 10/03/2025

footer_data_colors_pack_sizes: footer_data_colors_pack_sizes.value

footer_data_disclaimer: footer_data_disclaimer.value

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chiène
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu